

Antique Tobacco Oak Exposed Grain Flooring

Specification Sheet #10316

August 6, 2012



Design Professionals to specify this product use the following information:

product: Antique Tobacco Oak Exposed Grain Flooring

designate appropriate face widths, additional texture, if any, and factory finish or unfinished

contact: HistoricWoods by LunarCanyon 801-835-3476 kyle@historicwoods.net

Product Description:

1. **specie** a combination of red & white oak
2. **source: antique** 100% recycled primarily siding from tobacco drying barns
3. **moisture content** kiln-dried to 6-8% moisture content after the wood has been well seasoned in its previous use
4. **hardness** janka rating: 1290 (hard)
5. **character rating** 7.9 (rustic elements) our character scale rates floors on a 1 - 10 scale; a low number is a refined floor and a high number is very rustic
6. **grading** the appearance standards outlined here apply to a floor as a whole and not to individual boards
7. **knots** an unlimited amount of knots of any size are allowed; some knots are broken and may need filled or defected out by the installer
8. **holes** an unlimited amount of nail holes are allowed, but generally there are only a few nail holes per board; staining around fastener holes is common
9. **checks/cracks** some surface checking is allowed; cracks through the thickness of the board are allowed as long as the board is stable enough for nail down installation
10. **surface texture** the face will be planed mostly smooth, but will have some variances from critter tracks and checks; **additional textures available on this product:**
 - a. MooseTrackTexture™
 - b. ShadowTexture™
 - c. Wire-Brushed
 - d. Sculpted
 - e. Circle-Sawn
 - f. Band-Sawn
 - g. Pillowed edges
 - h. Square Plugs
11. **color** the color generally varies from tan to wheat to red
12. **grain** the majority of the wood will be flat or cathedral grain; some rift cut or quarter sawn boards may be included

Antique Tobacco Oak Exposed Grain Flooring

Specification Sheet #10316

August 6, 2012



13. **millwork** ¾" thick; the back of the board is milled mostly smooth with back outs; the ends of the boards will be cut square
14. **widths** 3" to 7" with custom sizes available; floors are usually produced with a combination of 3 or more face sizes with enough of each size to create a random pattern; stated widths may be adjusted +/- ½"
15. **lengths** 2' through 10'; with an average length of about 6'; boards up to 12' included if available
16. **installation** basic principles of installation for solid wood floors apply to this product and it should be installed according to the standard professional practices of your area; although, installers should be well experienced with custom wood floors and have artistic skill in board placement
17. **unfinished** this flooring product comes unfinished and is designed to be prepped and finished on site, however an option for a Factory Finish of Hard Oil UV Cured is available